

RECOMMENDED LUBRICANTS AND LUBRICANT CAPACITIES TABLE

RECOMMENDED LUBRICANTS

Items	Recommended lubricants
Engine oil	Engine oil displaying EOLCS certification mark or conforming to the API classification SH ECII, SH/CD ECII, SG ECII or SG/CD ECII (For further details, refer to "LUBRICANTS SELECTION" section)
Manual transaxle	Hypoid gear oil, SAE 75W-90 or 75W-85W conforming to API classification GL-4
Transfer	
Automatic transaxle	DIAMOND ATF SP or equivalent
Power steering	Automatic transmission fluid "DEXRON II"
Differential (rear axle)	Hypoid Gear Oil API classification GL-5 or higher Above -23°C (-10°F) SAE90, 85W-90, 80W-90 From -34°C (-30°F) to -23°C (-10°F) SAE 80W, 80W-90 Below -34°C (-30°F) SAE 75W
Brake and clutch	Conforming to DOT 3 or DOT 4
Engine coolant	DIA-QUEEN LONG-LIFE COOLANT (Part No. 0103044) or High quality ethylene-glycol antifreeze coolant
Door hinges, liftgate hinges	Engine oil

LUBRICANT CAPACITIES TABLE

Description		Metric measure	U.S. measure
Engine oil	Crankcase	4.0 dm ³	4.2 qts.
	Oil filter	0.3 dm ³	.32 qt.
	Oil cooler <Turbo>	0.3 dm ³	.32 qt.
	Total <Non-Turbo>	4.3 dm ³	4.5 qts.
	Total <Turbo>	4.6 dm ³	4.9 qts.
Cooling system (including heater and coolant reserve system)		8.0 dm ³	8.5 qts.
Manual transaxle	FWD	2.3 dm ³	2.4 qts.
	AWD	2.4 dm ³	2.5 qts.
Transfer	5M/T	0.27 dm ³	.29 qt.
	6M/T	0.30 dm ³	.32 qt.
Automatic transaxle		7.5 dm ³	7.9 qts.
Rear axle <AWD>		1.1 dm ³	1.16 qts.
Power steering	2WS	0.9 dm ³	.95 qt.
	4WS	1.45 dm ³	1.59 qts.
Fuel tank		75 dm ³	19.8 gals.